

## REWINDING TABLE

## REWINDING TABLE SERIE RT OR EV

### Features

- **Strong, reliable, easy and fast maintenance**
- **Manual or electric**
- **Respect of the film and user comfort**
- **Constant tension**



### ■ Inspection and verification tables for archives films

Table dedicated to work of archive films. Accurate construction for respect and safety of the film. Several options in relation with archive films

### ■ Capacity

Bi-format 16 and 35 mm. Film reels of 600 or 1200 m.

### ■ Manual or electric

This range of tables is ideal for handling negatives, positives or very delicate archival material.

Used for positive or negative film, a light box allows for a comfortable observation and assessment of passing films.

The speed can be controlled by hand with a handle, or electrically by foot pedal.

### ■ Mono or bidirectional

Manual M serie could be mono or bidirectional. Electrical M serie is monodirectional.

### ■ Retractable core

Hand lever to retract core upon take-up plates makes film manipulation easier. Only CTM-DEBRIE tables are equipped with this function. It facilitates the safe recovery of the reel.

### ■ Brake tension

Manual brake on the unwinder of electrical tables.

### ■ Multi-unit counter

It measures all film length (frame, feet, m and dm, time in 24-25 fps) for 16/35 mm format.

### ■ Film cleaning

Fitted with four PTR (optional) table can be used as a low-cost, environment friendly, safe film cleaner. As film moves through the rollers, dust, dirt and other unwanted particles are removed from both sides.

### ■ Options

OP80 - Multi-unit counter

OP222 - Support with PTR rollers to clean the film

OP813 - Metallic core with a retractable key

### ■ Technical specifications

	RT	EV
Capacity	600 m (2000ft)	600 m (2000 ft) or 1200 m (4000 ft)
Format	16/35mm	16/35 mm
Rewinding speed	300-500 m/min 1500 ft/ min.	400 m/min 1200 ft/min
Speed control	Handle Manual or Foot control	Manual or Foot control
<b>Dimensions</b>		
Length	1000 mm	1250 mm
Width	500 to 640 mm	600 mm
Height	900 mm	1508 mm
Weight	40 kg	80 kg

Power supply : 110/220 V - 50/60 Hz - 10 Amp

### ■ Range

Model	Designation
RT27	16/35 mm, 600 m, manual horizontal rewriter
RT28	16/35 mm, 600 m, electric horizontal rewriter
RT29	35 mm, 600 m, 2 motors, horizontal rewriter with constant tension
RT30	35 mm, 1200 m, 2 motors, horizontal rewriter with constant tension
EV600	16/35 mm, 600 m, vertical rewriter with 3 motors with constant tension
EV1200	16/35 mm, 1200 m, vertical rewriter with 3 motors with constant tension

